



I commenced a Survey of Section 5, T. 8 N., R. 6 W.  
for Elmer Peavy et al.

Henny G. Schlot  
Val Blanton  
C. B. Swain

Henny G. Schlot  
Surveyor Greene County.

Var.

Course.	Point of Beginning.	Chains Distance.	Corrected Bearings.
North	SE	77.64 to NE	
West	NE	80.40 to NW	
North	SW	78.80 to NN	
East	SW	80.13 to SE	

March 24 1923

I also surveyed for Arthur Mattson Part NE 1/4 NE 1/4 Sec 5 T 8 N R 6 W  
lying north of the Hows rill ditch (see plat.) and found it to contain 30.02 Acres

Henny G. Schlot S.

CORNER ESTABLISHED.	Monument.	Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
SW	Stone	+	Stone		N 87 1/2 E	18 1/2	Stone had been moved within
N 1/4 SW 1/4	"	+	Stone		East	25	
N 1/4	"	+	"		South	25	
N 1/4 NW 1/4	"	+	"		South	130	
NW	Iron Rod	+	"		South	46	
N 1/4 NW 1/4	"	+	"		South	28	
Cent. NW 1/4	"	+	Beach	16"	South	30	Old stone under road 5' new with us
way N 1/4 to Cent. NW 1/4	"	+	"		S 4 E	172 1/2	
S 1/4 NW 1/4	"	+	Stone		North	25	
N 1/4	"	+	"		South	25	
way N 1/4 to E 1/4 NW 1/4	"	+	"		North	25	
E 1/4 NW 1/4	"	+	" (clay stone)		East	10	
N 1/4 NE 1/4	"	+	"		North	38	
Cent. NE 1/4	"	+	"		S 70 W	25	
E 1/4 NE 1/4	Stake in ditch bank	+	"		S 40 E	25	
Cent. 1/4	Stone	+	Red Oak	18"	N 35 E	13 1/2	
E 1/4	"	+	Stone		East	25	
E 1/4 SE 1/4	Cement Block	+	"		North	25	
Cent. SE 1/4	Stone	+	"		West	25	
N 1/4 SE 1/4	"	+	Hickory	24"	S 75 W	22 3/4	
Cent. SW 1/4	"	+	Stone		South	25	
S 1/4 SW 1/4	"	+	"		North	30	
S 1/4	"	+	"		West	20	
S 1/4 SE 1/4	"	+	"		S 85 W	30	Stamp of Cloag's 13. Oak still there.
S 1/4 NE 1/4	"	+	Maple	20"	N 35 E	10	
SE cor.	in ditch	+	Stone		N 69 W	34	
NE	Iron pipe	+	P Oak	3"	S 38 E	40 1/2	
Cent. NE	Iron pipe	+	Cement Block		S 20 30 E	56 1/2	also cement block at top of pipe